

TEAMWORK IMPROVES SAFETY

Signatures

| 2 |
|----|
| 3 |
| 4 |
| 5 |
| 6 |
| 7 |
| 8 |
| 9 |
| 10 |
| 11 |
| 12 |
| 13 |
| 14 |
| 15 |
| 16 |
| 17 |
| 18 |
| |

KCA TOOL BOX TALK:

Standard Hand Signals for Cranes



STOP - With arm extended horizontally to the side, palm down, arm is swung back and forth.



EMERGENCY STOP - With both arms extended horizontally to the side, palms down, arms are swung back and forth.



HOIST - With upper arm extended to the side, forearm and index finger pointing straight up, hand and finger make small



RAISE BOOM - With arm extended horizontally to the side, thumb points up with other fingers closed.



SWING - With arm extended horizontally, index finger points in direction that boom is to swing.



RETRACT TELESCOPING BOOM - With hands to the front at waist level, thumbs point at each other with other fingers



RAISE THE BOOM AND LOWER THE LOAD - With arm extended horizontally to the side and thumb pointing up, fingers open and close while load movement is desired



DOG EVERYTHING - Hands held together at waist level.



LOWER - With arm and index finger pointing down, hand and finger make small circles.



LOWER BOOM - With arm extended horizontally to the side, thumb points down with other fingers closed.



EXTEND TELESCOPING BOOM - With hands to the front at waist level, thumbs point outward with other fingers closed.



TRAVEL/TOWER TRAVEL With all fingers pointing up, arm is extended horizontally out and back to make a pushing motion in



LOWER THE BOOM AND RAISE THE LOAD – With arm extended horizontally to the side and thumb pointing down, fingers open and close while load movement is desired



MOVE SLOWLY - A hand is placed in front of the hand that is giving the action signal.



USE AUXILIARY HOIST (whipline) – With arm bent at elbow and forearm vertical, elbow is tapped with other hand. Then regular signal is used to indicate desired action



CRAWLER CRANE TRAVEL, BOTH TRACKS -Rotate fists around each other in front of body; direction of rotation away from body indicates travel forward; rotation towards body indicates travel backward.



USE MAIN HOIST - A hand taps on top of the head. Then regular signal is given to indicate desired action.



ONE TRACK - Indicate track to be locked by raising fist on that side. Rotate other fist in front of body in direction that other track



TROLLEY TRAVEL - With palm up, fingers closed and thumb pointing in direction of motion, hand is jerked horizontally in direction trolley is to travel.

For more information visit OSHA REGULATIONS: 1926.1422

www.KeystoneContractors.com